

EXPRESS MAIL LABEL NO.

EF279580525US

MAGNETIC MEDIA WITH IMPROVED EXCHANGE COUPLING

Sudhir Malhotra
Donald C. Stafford
Zhengsheng Shan
Gerardo Bertero
David Wachenschwanz

Background of the Invention

This invention pertains to magnetic recording media such as magnetic disks.

Fig. 1 illustrates a magnetic recording medium 1 constructed in accordance with the prior art used for longitudinal data recording. Medium 1 comprises a substrate 2, an underlayer 3, a Co alloy magnetic layer 4 and a carbon protective overcoat 5. Also shown in Fig. 1 is a first region 4a of layer 4 magnetized in a first direction D1, a second region 4b magnetized in a second direction D2 opposite the first direction, and a transition region TR between regions D1 and D2. In magnetic recording, it is desirable for transition region TR to be as small as possible in order to maximize areal recording density. In general, the length of transition region TR is proportional to MrT/H_c , where Mr is the magnetic remanence of the Co alloy, T is the thickness of layer 4, and H_c is the coercivity of layer 4.

In order to reduce the length of region TR, one might be tempted to reduce MrT. Unfortunately, reducing MrT in medium 1 reduces the thermal stability of layer 4. In other words, reducing MrT reduces the ability of layer 4 to retain its magnetization state, and hence the data recorded in layer 4, as temperature increases. (Obviously, thermal stability is a highly desirable characteristic in a magnetic medium.)

Fig. 2 illustrates a second magnetic recording medium 20 in accordance with the prior art comprising a substrate 22, an underlayer 24, a lower Co alloy magnetic layer 26, a Ru layer 28, an upper Co alloy magnetic layer 30 and a carbon protective overcoat 32. Medium 20 is designed to facilitate simultaneous reduction of the length of transition region TR and increase in thermal stability. In particular, if Ru layer 28 has a thickness within a certain range (e.g. 0.3 to 1.0 nm), magnetic layers 26 and 30 are antiferromagnetically coupled to one another. Because of this, the length of transition region TR for medium 20 is proportional to $Mr_{26}T_{26} - KMr_{30}T_{30}$, where K is a proportionality constant, Mr_{26} is the magnetic remanence of layer 26, T_{26} is the thickness of layer 26, Mr_{30} is the magnetic remanence of layer 30 and T_{30} is the thickness of layer 30. (Constant K is related to the degree of antiferromagnetic coupling between layers 26 and 30.) However, the thermal stability of medium 20 increases as a function of $Mr_{26}T_{26} + K_2Mr_{30}T_{30}$. Thus, while the antiferromagnetic coupling permits one to reduce the length of transition region TR, it also improves thermal stability. (The antiferromagnetic coupling also improves the signal to noise ratio of medium 20.)

When recording data in medium 20 of Fig. 2, because of the antiferromagnetic coupling between layers 26 and 30, when one magnetizes a region within layer 30, e.g. as shown by arrow D3, the magnetization direction of layer 26 is in the opposite direction, e.g. as shown by arrow D4. Fig. 3 shows a hysteresis loop 40 for the structure of Fig. 2 if layers 26 and 30 were strongly coupled. As can be seen, as one increases the applied magnetic field H_{app} to medium 20, in portion P1 of hysteresis loop 40, both magnetic layers 26 and 30 are magnetized in the same direction D3. As one reduces the applied magnetic field H_{app} past point P2, the magnetization direction of layer 26 begins to switch

1 to direction D4. Portion P3 of hysteresis loop 40 shows the magnetic characteristics of
2 medium 20 as layer 26 changes magnetization direction in response to applied magnetic
3 field H_{app} . As applied magnetic field H_{app} is brought to zero (point P4), layer 26 is
4 magnetized in direction D4.

5 Fig. 4 shows a hysteresis loop of medium 20 if layer 26 were weakly
6 antiferromagnetically coupled to layer 30. As can be seen, the point P5 at which layer 26
7 switches magnetization direction (i.e. from direction D3 to D4) occurs at a much lower
8 applied magnetic field H_{app} in Fig. 4 than in Fig. 3. Weak coupling between layers 26
9 and 30 is disadvantageous because it increases the amount of time required to switch the
10 state of medium 20 to an antiferromagnetic state. In particular, it takes more time to
11 create a situation in which layer 30 is magnetized in direction D3 and layer 26 is
12 magnetized in direction D4. The magnetic recording medium relies on thermal energy to
13 switch the magnetization direction of layer 26 to direction D4. Further, weak coupling
14 can also create a situation in which layer 26 is not as completely magnetized as desired
15 when H_{app} is brought to zero.

16 It would be desirable to increase antiferromagnetic coupling between layers 26
17 and 30. One way to do this is to add pure Co layers 34 and 36 on each side of Ru layer
18 28, e.g. as provided in medium 20' shown in Fig. 5. Co layers 34 and 36 increase
19 antiferromagnetic coupling between layers 26 and 30. Unfortunately, Co layers 34 and
20 36 increase noise in medium 20' because of intergranular magnetic coupling in layers 34
21 and 36. It would be highly desirable to increase antiferromagnetic coupling between
22 layers 26 and 30 without suffering this increase in noise.

23

1 Summary

2 A magnetic recording medium in accordance with the invention comprises a
3 lower magnetic layer, an intermediate layer above the lower magnetic layer, and an upper
4 magnetic layer above the intermediate layer. The recording medium is typically a
5 magnetic disk. The upper and lower magnetic layers are ferromagnetic, and typically
6 comprise a Co alloy, a Fe alloy or a Ni alloy. The intermediate layer has the
7 characteristic that it induces antiferromagnetic coupling between the upper and lower
8 magnetic layers. In one embodiment, the intermediate layer comprises Ru.

9 In accordance with one aspect of the invention, the lower magnetic layer has a
10 high M_s in order to facilitate a high exchange field H_{ex} . (The exchange field is a
11 measure of the amount of coupling between the upper and lower magnetic layers.) In one
12 embodiment, the M_s of the lower magnetic layer is greater than or equal to 250 emu/cm^3 ,
13 and typically greater than 300 emu/cm^3 . The M_s of the lower magnetic layer can be less
14 than or equal to 2000 emu/cm^3 and generally less than or equal to 1400 emu/cm^3 .

15 It has been discovered that the high M_s values cooperate with the Ru intermediate
16 layer to provide strong antiferromagnetic coupling. (It is believed that the reason that a
17 high M_s promotes antiferromagnetic coupling is that coupling is a function of the density
18 of spins available for transport across the Ru. The higher the M_s , the greater the spin
19 density, the higher the amount of exchange across the Ru.)

20 In accordance with another aspect of the invention, the relation between dynamic
21 coercivity H_c and the exchange field H_{ex} is such that the lower magnetic layer will reach
22 its steady state magnetization condition after writing within one period of revolution of
23 the magnetic disk. In one embodiment, the lower magnetic layer will reach between 90

1 and 100% of its steady state magnetization condition within one period of revolution of
2 the magnetic disk. In another embodiment, the lower magnetic layer will reach between
3 95 and 100% of its steady state magnetization condition within one period of revolution
4 of the magnetic disk.

5 Hc of the lower magnetic layer is greater than or equal to zero but less than the
6 exchange field H_{ex} at recording switching times. The Hc of the lower magnetic layer at
7 recording switching times is typically less than or equal to about one half of the exchange
8 field for recording times. This facilitates quickly switching the lower magnetic layer to
9 its desired magnetization direction. (The Hc of the upper magnetic layer at recording
10 switching times is typically substantially greater than the Hc of the lower magnetic layer
11 at recording switching times.)

12 In accordance with another feature of the invention, the anisotropy constant K_u of
13 the upper magnetic layer is greater than 0.5×10^6 ergs/cm³ to provide good thermal
14 stability. In one embodiment, the K_u of the upper layer is greater than 1.0×10^6 ergs/
15 cm³. (The K_u of the upper magnetic layer should not be so high as to hamper writing,
16 and is typically less than 10^7 ergs/cm³.) The K_u of the lower layer can be smaller than
17 the K_u of the upper layer. For example, the lower magnetic layer can have a K_u of $1.0 \times$
18 10^4 ergs/cm³, 1.0×10^3 ergs/cm³, or even lower (but greater than or equal to 0 ergs/cm³).
19 (A lower K_u for the lower magnetic layer facilitates a lower coercivity, which in turn
20 facilitates ease of switching the magnetization direction of the lower magnetic layer.)

21 In one embodiment, the lower magnetic layer is a Co based alloy comprising
22 between 5 and 20 at. % Cr, 0 to 6 at. % Ta, 0 to 10 at. % B and 0 to 10 at. % Pt. The
23 alloy can contain between 0 and 10 at. % X, where X is one or more other elements. In

1 one embodiment, X is one or more of Nb, Ta, Cu, Mo, W, V, Si, C, Pd, Ru, Ir or Y.

2 Preferably, this alloy exhibits a Ms, Hc and Ku as described above.

3 In one embodiment, the upper magnetic layer is a Co based alloy comprising
4 between 10 and 30 at. % Cr, 8 to 20 at. % Pt and 0 to 20 at. % B. The upper magnetic
5 layer can comprise between 0 and 10 at. % X, where X is one or more other elements. X
6 can be one or more of Nb, Ta, Cu, Mo, W, V, Si, C, Pd, Ru, Ir or Y. Again, preferably
7 the alloy exhibits a Hc and Ku as described above.

8 A magnetic recording medium in accordance with another embodiment of the
9 invention comprises two or more Ru interlayers (e.g. two, three or more interlayers), each
10 sandwiched between two magnetic layers. The uppermost magnetic layer has the same
11 characteristics as described above for the upper magnetic layer. The magnetic layers
12 below the Ru interlayers have the same characteristics as described above for the lower
13 magnetic layer.

14 Although the foregoing description refers to upper and lower magnetic layers,
15 either or both of the upper and lower magnetic layers can comprise a plurality of
16 sublayers of different compositions. Thus, for example, if the lower layer comprises a
17 plurality of sublayers, the effective composite Ms of the sublayers combined should be a
18 value as described above. Similarly, if the upper or lower layer comprises a plurality of
19 sublayers, the effective composite dynamic Hc (e.g. at recording times) and Ku of the
20 sublayers should be a value as described above.

21

1 Brief Description of the Drawings

2 Fig. 1 illustrates in cross section a first magnetic recording medium constructed in
3 accordance with the prior art.

4 Fig. 2 illustrates in cross section a second magnetic recording medium constructed
5 in accordance with the prior art comprising a Ru layer for facilitating antiferromagnetic
6 coupling between upper and lower magnetic Co alloy layers.

7 Fig. 3 is a hysteresis loop for a magnetic recording medium if upper and lower
8 magnetic layers were strongly antiferromagnetically coupled to one another.

9 Fig. 4 is a hysteresis loop for a magnetic recording medium if upper and lower
10 magnetic layers were weakly antiferromagnetically coupled to one another.

11 Fig. 5 illustrates in cross section a third magnetic recording medium constructed
12 in accordance with the prior art comprising a Co layer formed between magnetic Co alloy
13 layers and a Ru layer.

14 Fig. 6 illustrates in cross section a magnetic recording medium constructed in
15 accordance with a first embodiment of the invention.

16 Fig. 7 illustrates in cross section a magnetic recording medium in accordance with
17 a second embodiment of the invention.

18 Fig. 8A illustrates the effect of H-Field Sweep Rate on MrT in a magnetic
19 recording medium in which the lower magnetic film has an Ms of 300 emu/cm³.

20 Fig. 8B illustrates the effect of H-Field Sweep Rate on MrT for a magnetic
21 recording medium in which the lower magnetic film has an Ms of 550 emu/cm³ and
22 therefore a higher exchange field than that of Fig. 8A.

Fig. 9A illustrates the fundamental harmonic amplitude decay for a magnetic recording medium in which the exchange field is about 300 Oe.

Fig. 9B illustrates the fundamental harmonic amplitude decay for a magnetic recording medium in which the exchange field is about 2500 Oe.

Fig. 10 illustrates a magnetic recording medium constructed in accordance with third embodiment of the invention.

Fig. 11 illustrates a magnetic recording medium constructed in accordance with a fourth embodiment of the invention.

Fig. 12 illustrates a magnetic disk in accordance with the present invention incorporated into a disk drive.

Detailed Description

Referring to Fig. 6, a magnetic recording medium 100 in accordance with the invention comprises a non-magnetic substrate 102, an underlayer 104, a lower magnetic layer 106, an intermediate layer 108, an upper magnetic layer 110 and a carbon protective overcoat 112. Substrate 102 can be an aluminum alloy substrate coated with an electroless plated nickel-phosphorus alloy. Alternatively, substrate 102 can be glass, glass-ceramic, or other appropriate material. (Typically, the above-mentioned layers are formed on both the top and bottom surfaces 102a, 102b of substrate 102, but only the layers on top surface 102a are shown for ease of illustration.)

Magnetic layers 106 and 110 are typically Co, Fe or Ni-based alloys. Layer 106 is typically between 2 and 8 nm thick, and layer 110 is typically 6 to 30 nm thick. Intermediate layer 108 is typically Ru or a Ru alloy (e.g. consisting essentially of Ru).

1 (Layer 108 is typically between 0.3 and 1.0 nm thick.) For the case of Co alloys, layers
2 106 and 110 typically have a HCP crystal structure and a $11\bar{2}0$ orientation.

3 Underlayer 104 is typically Cr or a Cr alloy such as Cr-Mo. In one embodiment,
4 underlayer 104 comprises $\text{Cr}_{80}\text{Mo}_{20}$ (at. %), has a thickness of 10 nm, and a BCC crystal
5 structure.

6 As mentioned above, in accordance with one aspect of the invention, magnetic
7 recording medium 100 exhibits a high exchange field H_{ex} . This is typically
8 accomplished (at least in part) by ensuring that magnetic layer 106 exhibits a high M_s ,
9 preferably greater than or equal to 250 emu/cm^3 , and typically greater than or equal to
10 300 emu/cm^3 , and in one embodiment, greater than 350 emu/cm^3 . Typically, the M_s of
11 layer 106 is less than 2000 emu/cm^3 and for the case in which layer 106 comprises
12 primarily Co, the M_s of layer 106 is less than about 1400 emu/cm^3 . (While the lower
13 magnetic layer 106 can have a higher M_s than upper magnetic layer 110, upper magnetic
14 layer 110 typically has a higher magnetic moment M_sT (magnetization times thickness)
15 than lower magnetic layer 106.)

16 Also as mentioned above, the coercivity H_c of layer 106 is typically greater than
17 or equal to zero but less than the exchange field H_{ex} at recording switching times. The
18 recording switching time is the amount of time one exposes a point on the recording
19 medium to a write magnetic field. For the case of a magnetic disk in a disk drive during
20 recording, the recording switching time is approximately the amount of time it takes a
21 point on the spinning disk to travel the length of the head write gap. (Disks in currently
22 manufactured disk drives spin at a rate between about 4,000 and 15,000 rpm. This
23 corresponds to a period of rotation of 15 milliseconds to 4 milliseconds.) For disk drives

Co. For example, layer 108 can be $\text{CoCr}_{16}\text{Ta}_4$. (As used herein, $\text{CoCr}_{16}\text{Ta}_4$ means an alloy comprising 16 at. % Cr, 4 at. % Ta, and the remainder Co.) Alternatively, layer 106 can have 0 to 10 at. % X, where X is one or more other elements, e.g. one or more of Cu, Mo, W, V, Si, C, Pd, Ru, Ir or Y. Layer 106 can have a K_u greater than or equal to 1.0×10^4 ergs/cm³, e.g. between 0.5×10^6 and 1.0×10^6 ergs/cm³.

In an alternative embodiment, lower magnetic layer 106 can be another magnetically soft material with intergranular decoupling, e.g. suitably modified NiFe (permalloy), FeAlSi (sendust), CoTaZr, FeTaC, NiFeNb, CoFe, NiCrFe, NiV, CuNi, FeRh or PtMn.

Magnetic layer 110 is also typically a Co alloy layer and has a high M_s . In one embodiment, layer 110 has between 10 and 30 at. % Cr, 8 to 20 at. % Pt, 0 to 20 at. % B and the balance Co. For example, layer 110 can be $\text{CoCr}_{15}\text{Pt}_{11}\text{B}_{11}$. Alternatively, layer 110 can also include 0 to 10 at. % X, where X is one or more other elements, e.g. one or more of Nb, Ta, Cu, Mo, W, V, Si, C, Pd, Ru, Ir or Y. In one embodiment, layer 110 has a high K_u , e.g. a K_u greater than about 1.0×10^6 erg/cm³, e.g. between 1.0×10^6 and 1.0×10^7 erg/cm³ to promote thermal stability. (The K_u of layer 110 is greater than that of layer 106.) Layer 110 also has a high M_s , e.g. greater than 300 emu/cm³. In one embodiment, layer 110 has a M_s between 300 and 650 emu/cm³.

Figs. 8A and 8B illustrate the effect of H-Field Sweep-Rate on MrT for magnetic recording media with lower and higher M_s , respectively. In particular, the H_{app} -field sweep rate for Figs. 8A and 8B varied between 0.1 seconds to several seconds. The magnetic disk of Fig. 8B had a lower magnetic layer exhibiting an M_s of about 550/cm³. Because of this, antiferromagnetic coupling between the upper and lower magnetic layers

was relatively high, and the lower magnetic layer generally switched magnetization directions before the applied field H_{app} reached 0 Oe. In other words, M_r was generally independent of the sweep rate.

In contrast, the lower magnetic layer of Fig. 8A had a lower M_s (300 emu/cm³) and thus exhibited less antiferromagnetic coupling. Therefore, in the context of the magnetic medium of Fig. 8A (with a lower level H_c close to the exchange field strength), M_r was more dependent on sweep rate—an undesirable characteristic because it does not allow the lower layer to switch quickly to the desired state.

Figs. 9A and 9B illustrate the fundamental harmonic amplitude decay for magnetic recording media with an exchange coupling field H_{ex} of 300 Oe and 2500 Oe, respectively. The Y axis of Figs. 9A and 9B represents the normalized fundamental harmonic amplitude. In other words, after data is recorded in the magnetic recording medium, the amplitude of the recorded signal is repeatedly read back. The Y axis represents subsequent read-back values divided by the initial read-back value. Data in Fig. 9A was generated for different data recording densities. As can be seen, the extent to which amplitude dropped over time was highly dependent on recording density. For example, for a density of 3 kFCI (3000 flux changes per inch), over a 20 second time period, the normalized fundamental harmonic amplitude dropped to approximately 0.73, whereas for a density of 289 kFCI, the normalized fundamental harmonic amplitude only dropped to a value of about 0.98 after 20 seconds. The reason for this difference is that the demagnetizing field increases as recording density increases (i.e. as the size of a magnetized region decreases). This demagnetizing field helps to switch the magnetization direction in lower magnetic layer 106. If the demagnetizing field is small

1 (as in the case of a low recording density), it provides less assistance in switching the
2 magnetization direction of magnetic layer 106, and therefore it takes magnetic layer 106
3 more time to settle into a final magnetization state (i.e. magnetized in direction D4).

4 As mentioned above, the data of Fig. 9A was generated for a disk exhibiting
5 relatively low antiferromagnetic coupling between the upper and lower magnetic layers,
6 e.g. for an exchange field of about 300 Oe. In Fig. 9B, the disk exhibited relatively high
7 antiferromagnetic coupling between the upper and lower magnetic layers, i.e. about 2500
8 Oe. This relatively high coupling promotes switching of the magnetization direction of
9 the lower magnetic layer 106. Therefore, even for fairly low recording densities (e.g. 3
10 kFCI), the normalized fundamental harmonic amplitude after 20 seconds is about 0.91,
11 compared to 0.73 for Fig. 9A. A significant change in normalized fundamental harmonic
12 amplitude is undesirable because it means that medium 100 may exhibit inadequate
13 switching and signal stability.

14 Fig. 7 illustrates a magnetic recording medium 100a constructed in accordance
15 with another embodiment of the invention. Medium 100a is similar to medium 100 of
16 Fig. 6, but includes an optional seed layer 105 formed between underlayer 104 and lower
17 magnetic layer 106. Seed layer 105 can be as discussed in U.S. Patent 6,150,015, issued
18 to Bertero et al. on November 21, 2000, incorporated herein by reference.

19 Also shown in Fig. 7 is a magnetic layer 120 formed on magnetic layer 110.
20 Magnetic layer 120 enables one to tailor medium 100a with enhanced flexibility so that it
21 exhibits desired H_c, MrT, noise or PW50. In the embodiment of Fig. 7, layer 120 can be
22 10 nm thick, and can comprise CoCr₂₄Pt₁₂B₈, while layer 110 can be 6 nm thick and

comprise $\text{CoCr}_{15}\text{Pt}_{11}\text{B}_{12}$. Alternatively, magnetic layer 120 could comprise another alloy such as CoCrPtTaB , other Co alloys, a Ni alloy or a Fe alloy.

Fig. 10 illustrates a magnetic recording medium in accordance with another embodiment of the invention. In Fig. 10, a medium 100b comprises substrate 102, a 8 nm thick Cr-Mo_{20} underlayer 104, a 2 nm thick $\text{CoCr}_{25}\text{Ta}_2$ seed layer 105, a 4 nm thick $\text{CoCr}_{16}\text{Ta}_4$ magnetic layer 106, a 0.8 nm thick Ru intermediate layer 108, magnetic sublayers 110a, 110b and 110c and a protective overcoat 112. Merely by way of example, sublayers 110a, 110b and 110c can be 2 nm thick $\text{CoCr}_{16}\text{Ta}_4$, 6 nm thick $\text{CoCr}_{23}\text{Pt}_{11}\text{B}_5\text{Ta}_1$ and 6 nm thick $\text{CoCr}_{15}\text{Pt}_{10}\text{B}_{12}$. In this embodiment, sublayers 110a, 110b, and 110c (which make up upper magnetic layer 110) are magnetized in a first direction, while lower magnetic layer 106 is magnetized in a second direction opposite the first direction by virtue of antiferromagnetic coupling resulting from intermediate layer 108. Thus, it is seen that the upper magnetic layers can comprise a plurality of sublayers. In an alternative embodiment, lower layer 106 can also comprise a plurality of sublayers.

In this patent, the term "layer structure" will refer to a structure comprising one layer or a plurality of layers that are ferromagnetically coupled to one another. Thus, as used herein, lower layer 106 is a layer structure, and layers 110a, 110b and 110c collectively are a layer structure.

Fig. 11 illustrates a medium 100c comprises a lowermost magnetic layer 106', a lower Ru layer 108', a magnetic layer 106'', a Ru layer 108'' an uppermost magnetic layer 110 and a protective overcoat 112. For the embodiment of Fig. 11, the magnetic characteristics of layer 110 are as described above for the embodiments of 6, 7 and 10.

1 Ru layers 108' and 108'' are typically between 0.3 and 1.0 nm thick, and facilitate the
2 above-described antiferromagnetic coupling phenomenon. Layers 106' and 106'' have
3 the same magnetic characteristics as those described above for layer 106 in the
4 embodiments of Figs. 6, 7 and 10. If one writes data in layer 110 such that the
5 magnetization direction is D5 and then removes the applied write magnetic field H_{app} , the
6 magnetization direction in layer 106'' will be direction D6, which is in the opposite
7 direction of D5. The magnetization direction in layer 106' will be direction D7, which is
8 the opposite of direction D6.

9 While Fig. 11 shows two Ru layers 108', 108'' sandwiched between magnetic
10 layers, in other embodiments, three or more Ru layers can be provided, each sandwiched
11 between magnetic layers. The benefit of this embodiment is to create greater thermal
12 stability in medium 100c.

13 In the embodiments of Figs. 6, 7, 10 and 11, the magnetization direction in layer
14 106 (or layers 106' and 106'' for the case of Fig. 11) is controlled by the magnetization
15 direction in layer 110. In particular, layer 110 is antiferromagnetically coupled to layer
16 106 (or to layer 106'' for the case of Fig. 11) and the magnetization in layer 110 forces
17 layer 106 (106'') to assume a magnetization direction that is opposite to the direction of
18 layer 110. Similarly, the antiferromagnetic coupling between layers 106' and 106'' cause
19 layer 106' to have a magnetization direction that is opposite to the magnetization
20 direction of layer 106''. In effect, the magnetization directions for layers 106, 106' and
21 106'' are determined by the magnetization direction of layer 110. Thus, it can be said that
22 layers 106, 106' and 106'' are "slave layers", i.e. layers whose steady state magnetization

direction (after the write field has been removed) is determined either directly or indirectly by a "master layer", e.g. layer 110.

Magnetic recording media in accordance with the invention are typically manufactured using a vacuum deposition technique such as sputtering. For example, one or more substrates can be placed in a substrate carrier that carries the substrates past a set of sputtering targets to deposit the various layers of the magnetic disk. The targets have compositions that are substantially the same as the composition of the layers that they are used to produce. Sputtering is typically accomplished in an atmosphere comprising an inert gas such as argon. (Other gases may be present in the sputtering chamber as well.)

A magnetic medium in accordance with the invention (e.g. medium 100, 100a, 100b or 100c) is typically in the form of a disk incorporated within a disk drive, e.g. disk 200 drive 201 (Fig. 11). Disk drive 201 comprises magnetic disk 200 mounted on a spindle 202 which is coupled to a motor 204 for rotating disk 200. A pair of read-write heads 206a, 206b are positioned proximate to disk 200 for reading data from and writing data to magnetic layers on each side of disk 200. Heads 206a, 206b are mounted on suspensions 208a, 208b, which in turn are mounted on actuators (e.g. rotary or linear actuators 210a, 210b) for moving heads 206a, 206b over desired data recording tracks of disk 200. Although only one disk 200 is shown in drive 201, drive 201 can contain multiple disks.

While the invention has been described with respect to specific embodiments, those skilled in the art will recognize that changes can be made in form and detail without departing from the spirit and scope of the invention. For example, the disk substrate can be textured, e.g. using mechanical, chemical, and/or laser texturing techniques. Different

1 types of protective overcoats (e.g. carbon, hydrogenated or nitrogenated carbon, or
2 zirconia) can be applied to upper magnetic layer 110. A lubricant can be applied to the
3 top surface of the disk (e.g. a perfluoropolyether lubricant). The various layers of the
4 magnetic disk can be formed by any of a number of deposition techniques, e.g. a vacuum
5 deposition technique such as sputtering. Different segregants can be added to one or
6 more of the magnetic layers to break exchange coupling between the grains, e.g. boron,
7 silica, alumina, zirconia, or other oxides such as tantalum oxide, cobalt oxide, etc.
8 Different magnetic layer thicknesses can be employed. Different aspects or features of
9 the invention can be practiced independently of one another. Accordingly, all such
10 changes come within the invention.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000